

Applicant: Firooz RASOULI  
Application Serial No. 09/873,476  
Filed: June 4, 2001  
Date: May 24, 2004

### **IN THE CLAIMS**

A complete listing of all claims pending, amended and cancelled is included as follows:

- 1) (canceled) A virtual remote touching system, for enabling a broadcasting user to transmit tactile characteristic information to a receiving user, comprising:
  - at least one sensing broadcasting unit, capable of sensing the broadcasting user's tactile characteristics and creating electronic simulation data of said characteristics;
  - a transmitting system for sending said electronic simulation data from said sensing broadcasting unit to a receiving device;
  - at least one receiving simulating unit, capable of receiving electronic simulation data, such that an engaging receiving user can touch the simulated tactile characteristics of the broadcasting user.
- 2) (currently amended) The virtual remote touching system of claim [[1]] 42, wherein the simulation data is electronically transmitted between the broadcasting unit and receiving unit by using the Internet.
- 3) (currently amended) The virtual remote touching system of claim [[1]] 42, wherein the simulation data stream is electronically exchanged between the broadcasting unit and the receiving unit using a real-time Internet application, such that the receiving user can instantly touch simulated tactile characteristics of the broadcasting user.
- 4) (currently amended) The virtual remote touching system of claim [[1]] 42, wherein said sensing broadcasting unit comprises a broadcasting device, a base, at least one sensor, and a data acquisition device.
- 5) (original) The virtual remote touching system of claim 4, wherein said broadcasting

Applicant: Firooz RASOULI  
Application Serial No. 09/873,476  
Filed: June 4, 2001  
Date: May 24, 2004

device engageably receives at least one body part from said broadcasting user, said at least one tactile detecting sensor is connected to the broadcasting device, so as to detect selected characteristic data of the at least one engaging body part, said broadcasting device generates an indicating signal, and said indicating signal is received by said data acquisition device.

6) (currently amended) The virtual remote touching system as in claim ~~[[1]]~~ 42, wherein said simulating unit comprises a processing system, a controller, a receiving device, a base, an at least one sensor and said receiving device is configured to engageably receive an at least one interfacing body part from said receiving user.

7) (currently amended) The virtual remote touching system of claim 6, wherein said at least one sensor is connected to said broadcasting device for detecting selected tactile characteristic data of said at least one ~~interfacing~~engaging body part.

8) (original) The virtual remote touching system of claim 7, wherein said data acquisition device receives a signal from a connected at least one sensor and transmits said information to said transmitting system.

9) (original) The virtual remote touching system of claim 8, wherein said at least one sensor is a temperature sensor for detecting the temperature of the broadcasting user's at least one engaging body part and relaying an indicating signal to said data acquisition device.

10) (original) The virtual remote touching system of claim 8, wherein said at least one sensor is a moisture sensor for detecting the moisture of the broadcasting user's at least one engaging body part and relaying an indicating signal to said data acquisition device.

11) (original) The virtual remote touching system of claim 8, wherein said at least one

Applicant: Firooz RASOULI  
Application Serial No. 09/873,476  
Filed: June 4, 2001  
Date: May 24, 2004

sensor is a surface sensor, for detecting the roughness characteristic of the at least one engaging body part and relaying an indicating signal to said data acquisition device.

12) (original) The virtual remote touching system of claim 8, wherein said at least one sensor is a hardness sensor, for detecting the hardness of the at least one engaging body part and relaying an indicating data signal to said data acquisition device.

13) (original) The virtual remote touching system of claim 12, wherein an at least one tactile detecting sensor cooperatively engages said receiving device, such that said detecting sensor sends an indicating data signal to said controller, wherein said controller receives said indicating signal and compares data received from said indicating signal to received electronic simulation data.

14) (original) The virtual remote touching system of claim 12, wherein receiving device is comprised of a synthetic polymeric material.

15) (original) The virtual remote touching system of claim 12, wherein said at least one sensor is a temperature sensor for detecting the temperature of the receiving device and relay an indicating signal to said controller.

16) (original) The virtual remote touching system of claim 12 wherein said at least one sensor is a moisture sensor for sensing the moisture content of the receiving device and relaying an indicating signal to said controller.

17) (original) The virtual remote touching system of claim 12 wherein said at least one sensor is a hardness sensor for detecting the hardness of the inner surface of the receiving device and relaying an indicating signal to said controller.

18) (original) The virtual remote touching system as in claim 12 wherein said receiving

Applicant: Firooz RASOULI  
Application Serial No. 09/873,476  
Filed: June 4, 2001  
Date: May 24, 2004

interface has a hand shaped configuration.

19) (original) The virtual remote touching system as in claim 12 wherein said receiving interface has lip-like shaped configuration.

20) (original) The virtual remote touching system as in claim 15, further comprising a moisturizing element in connective association with said receiving device, such that a signal from said controller causes the moisturizing element to create moisture into said receiving device.

21) (currently amended) The virtual remote touching system as in claim 12, further comprising a moisture removing apparatus, said moisture removing apparatus is electronically connected to said controller, such that when said controller sends a controlling signal to said moisture-removing apparatus, said moisture removing apparatus blows drying air in the direction of the receiving device to remove moisture from the receiving device.

22) (original) The virtual remote touching system as in claim 12, further comprising a temperature regulating apparatus, said temperature apparatus is electronically connected to said controller, such that when said controller sends a controlling signal to said temperature regulating apparatus, said apparatus increases or decreases the temperature of the interfacing device.

23) (original) The virtual remote touching system as in claim 12, wherein interfacing device is comprised of a flexible polymer that is capable of responsively deforming in response to a controlling signal, thereby creating a simulation of the texture if the broadcaster's engaging body part.

24) (currently amended)      A tactile sending unit for use with a virtual remote touching

Applicant: Firooz RASOULI  
Application Serial No. 09/873,476  
Filed: June 4, 2001  
Date: May 24, 2004

system, for two or more users to transmit, to each other, tactile characteristic information,  
the remote touching system comprising:

at least one tactile sensing unit for each user;  
the at least one tactile sensing unit; comprising[[:]];  
an interfacing device;  
an at least one sensor for detecting tactile data of an engaging user and sending an  
indicating signal;  
a data acquisition apparatus for receiving said indicating signal from said at least  
one sensor;  
computing means, associated with each sensing unit, for converting the tactile  
data determined by a sensing unit into an indicating signal;  
at least one broadcasting unit for each user for sending the indicating signal;  
at least one substantially identical receiving unit for each user for receiving the  
indicating signal;  
second computing means, associated with each receiving unit, the second  
computing means and receiving unit being capable of converting the broadcast indicating  
signal into a faithful reproduction of the first determined tactile data whereby one user  
can virtually feel the tactile characteristics of another user.

~~A tactile sensing unit, for sensing an engaging user's tactile characteristic data of a~~  
~~user; comprising: an interfacing device; an at least one sensor for detecting tactile data of~~  
~~an engaging user and sending an indicating signal; a data acquisition apparatus for~~  
~~receiving said indicating signal from said at least one sensor.~~

25) (original) The tactile sensing unit of claim 24, wherein the sensing unit is a  
transmitting unit, comprising a broadcasting device, a base, an at least one sensor, and a  
data acquisition device;

wherein said broadcasting device engageably receives said at least one body part from  
said broadcasting user; wherein said at least one sensor is connected to said broadcasting  
device, to detect tactile characteristic data of at least one engaging body part and creating

Applicant: Firooz RASOULI  
Application Serial No. 09/873,476  
Filed: June 4, 2001  
Date: May 24, 2004

an indicating signal to be received by said data acquisition device.

26) (original) The tactile sensing unit of claim 24, wherein said at least one sensor is a temperature sensor for detecting the temperature of the broadcasting user's at least one engaging body part and relaying an indicating signal to said data acquisition device.

27) (original) The tactile sensing unit of claim 24 wherein at least one sensor is a moisture sensor for detecting the moisture of the broadcasting user's at least one engaging body part and relays an indicating signal to connect said data acquisition device.

28) (original) The tactile sensing unit of claim 24, wherein at least one sensor is a hardness sensor that detects the hardness of the at least one engaging body part and relays an indicating signal to said data acquisition device.

29) (original) The tactile sensing unit of claim 24, wherein at least one sensor is a movement sensor capable of detecting the movement or vibration of the engaging body part and relaying an indicating signal to said data acquisition device.

30) (original) The tactile sensing unit of claim 24, wherein the interfacing device has a hand-shaped configuration for engagement with an interfacing user's hand.

31) (original) The tactile sensing unit of claim 24, wherein the interfacing device has a lip-shaped configuration shape for engagement with an interfacing user's lips.

32) (original) The tactile sensing unit of claim 24, wherein said tactile sensing device is a simulating unit for receiving tactile data from a source, wherein said simulating unit comprises a receiving device, a base, an at least one sensor, a data processing system and a controller, wherein said data processing system receives electronic tactile simulation data from a remote source, wherein said at least one sensor detects selected tactile

Applicant: Firooz RASOULI  
Application Serial No. 09/873,476  
Filed: June 4, 2001  
Date: May 24, 2004

characteristics and sends a tactile indicating data signal to said controller, wherein said controller compares said electronic tactile simulation data to that of received tactile indicating data and sends a generating signal to an at least one selected regulating apparatus.

33) (original) The tactile sensing unit of claim 30, wherein said at least one sensor is a temperature sensor for detecting the temperature of the receiving user's said at least one engaging body part and relays an indicating data signal to said controller.

34) (original) The tactile sensing unit of claim 30, wherein said at least one sensor is a moisture sensor for detecting the moisture of the receiving user's said at least one engaging body part and relays an indicating data signal to said controller.

35) (original) The tactile sensing unit of claim 30, wherein said at least one sensor is a surface sensor, for detecting the roughness characteristic of receiving user's said at least one engaging body part and relaying an indicating data signal to said controller.

36) (original) The tactile sensing unit of claim 30, wherein a hardness sensor detects the hardness of receiving user's said at least one engaging body part and relays an indicating data signal to said controller.

37) (original) The tactile sensing unit of claim 30, wherein a vibration sensor detects the movement of the receiving user's said at least one engaging body part and relays an indicating data signal to said controller.

38) (original) The tactile sensing unit of claim 30, wherein said regulating device is a moisture regulator adjacent to said interfacing device, comprised of a moisturizing element reactive to heat such that when heated the moisturizing element releases moisture.

Applicant: Firooz RASOULI  
Application Serial No. 09/873,476  
Filed: June 4, 2001  
Date: May 24, 2004

39) (original) The tactile sensing unit of claim 30, wherein said interfacing device is comprised of a flexible polymer that responsively deforms responsive to a signal, thereby forming the texture of a broadcaster's engaging body part.

40) (original) The tactile sensing unit of claim 29, wherein said interfacing device is connected to a temperature regulating device such that the surface temperature of the interfacing device can be controlled to simulate the temperature of the broadcasting user's engaging body part.

41) (currently amended) A method for enabling users to remotely virtually touch, comprising the steps of:

providing a broadcasting-sensing unit comprising an interfacing device capable of receiving a broadcasting user's interfacing body part and sensing tactile characteristics of the body part for each of at least two users;

positioning the interfacing body part into an engaging position with the interfacing device, such that the interfacing device can detect tactile characteristics of the interfacing body part;

detecting tactile characteristics of the broadcasting user's interfacing part, such that a data signal containing the detected simulation data is generated;

providing a data acquisition device, for each of at least two users, the acquisition device being capable of receiving the data signal and converting the signal into an electronic data form;

transferring the data signal to the data acquisition device~~board~~;

converting the signal into transferable simulation data stream;

transferring the simulation data stream to a transmitting device;

providing a receiving-simulating unit having a receiving interface, for each of at least two users, capable of receiving data and converting the simulation data into a tactile



· Applicant: Firooz RASOULI  
Application Serial No. 09/873,476  
Filed: June 4, 2001  
Date: May 24, 2004

simulation, such that a receiving user can touch simulated tactile qualities of the broadcasting user;

transmitting the simulation data to the receiving-simulating unit having a controller capable of converting the data into indicating electronic signals;

positioning the receiving user's body part in an associated engagement with the receiving-simulating interface;

providing a simulating device capable of simulating tactile characteristics;

converting the simulation data into an indicating signal and transmitting the indicating signal to the simulating device;

wherein, when a broadcasting user positions his body part in touching engagement with the broadcasting unit, electronic simulation data is generated and transmitted to a simulating unit having simulation devices, such that a receiving user who engages the simulating unit can feel a simulation of the touch of the broadcasting user.

42 (new) A virtual remote touching system, for two or more users to transmit, to each other, tactile characteristic information, the remote touching system comprising:

at least one substantially identical sensing unit for each user, each sensing unit being capable of determining the first tactile characteristics of its user;

computing means, associated with each sensing unit, for converting the tactile characteristics determined by a sensing unit into electronic simulation data;

at least one broadcasting unit for each user for sending the electronic simulation data from one user to another;

at least one substantially identical receiving unit for each user for receiving electronic simulation data;

second computing means, associated with each receiving unit, the second computing means and receiving unit being capable of converting the broadcast electronic simulation data into a faithful reproduction of the first determined tactile characteristics;

whereby one user can virtually feel the tactile characteristics of another user.